



Piranha

Submersible Dewatering Pumps

Model P-2000-50

14.9 kw / 4 & 6 Inch Discharge (100 & 150 mm)
220/380/415/500v three phase 50 hz

Home Of Piranha Pumps www.piranhapumps.com

Pump Construction

- Housing 356T6 Al Alloy
- Mechanical Seals Silicon Carbide
- Impeller Heat Treated 17-4 PH SS
- Rotor Shaft 416 SS
- Lower Diffuser Nitrile Rubber – Adjustable
- Discharge Lining Nitrile Rubber
- Strainer 316 SS 10x32 mm Openings
- Hardware 304 SS
- Pump Weight 104 kg
- Lifting Handle 316 SS With Rubber Grip



Motor Specifications

- Motor Seal Double Oring
- Rating 3 Phase 14.9 kw
- Voltage 220/380/415/500
- Current F.L.A. 42/25/23/17.5
- Thermal Overload 2 Integral Switches
- Circuit Breaker Short Circuit, Locked Rotor, & Overload Protection
- RPM 2875
- Insulation Class F / 155 Degrees C
- Power Cable 15.2 m 6/3 SOW-A
- Control NEMA 4X

Piranha pump model P2000, HV & HH
 14.9 kw, 50 hz

