



Piranha

Submersible Dewatering Pumps

Model P-650

6.5 HP / 3 & 4 Inch Discharge

230v/460v/575v three phase

Home Of Piranha Pumps www.piranhapump.com

Pump Construction

- Housing 356T6 Al Alloy
- Mechanical Seals Silicon Carbide
- Impeller Heat Treated 17-4 PH SS
- Rotor Shaft 416 SS
- Lower Diffuser Nitrile Rubber – Adjustable
- Discharge Lining Nitrile Rubber
- Strainer 316 SS 1/4" x 1" Openings
- Hardware 304 SS
- Pump Weight 80 Lbs
- Lifting Handle 316 SS With Rubber Grip
- Dimensions: HV 25.5" H x 10.75" D
- Dimensions: HH 22.75" H x 10" D



Motor Specifications

- Motor Seal Double Oring
- Rating 3 Phase 6.5 HP
- Voltage 230 / 460 Volt
- Current F.L.A. 17.8 / 8.9
- Thermal Overload 2 Integral Switches
- Circuit Breaker Short Circuit, Locked Rotor, & Overload Protection
- RPM 3450
- Insulation Class F / 310 Degrees F
- Power Cable 50' 12/4 SOW-A
- Control NEMA 4X

Piranha Model P-650 HV & HH
6.5 HP - 230 / 460 Volt

